


LR14AD POWERLINE





DIMENSIONS (MM)





Specifications	LR14 / L / C / AM2 / BABY / MN1400 / 14A / 14AC
Made in	Belgium
Type	Alkaline Foil
Nominal voltage [V]	1.5
Electrolyte	Potassium Hydroxide
Average weight [g]	66.0
Storage temp. range	+10°C (50°F) ~ +25°C (77°F)
Operating temp. range	-20°C (-4°F) ~ +55°C (131°F)
Average Impedance	+/- 100 mΩ @ 1kHz fresh
Heavy metals	No added Mercury [Hg], Cadmium [Cd] or Lead [Pb]
Compliant to	IEC 60086-1, IEC 60086-2, IEC 60086-5 non dangerous goods regulation EC directive 91/157 EC & 98/101 EC Nordic Ecolabel
Recommended cut off voltage	0.8V per cell (0.9V per cell for multi series usage)

LR14AD POWERLINE

TYPICAL DISCHARGE VALUES






DISCHARGE TEMPERATURE CHARACTERISTICS



The information herein is believed to be correct. However no warranty is made, either expressed or implied, regarding the accuracy of the results to be obtained from the use of such information. Test results are strictly according to IEC conditions. Capacities of batteries depend on drain, temperature and cut-off voltage. Data are subject to change.

LR14AD POWERLINE

DISCHARGE TEMPERATURE CHARACTERISTICS



The information herein is believed to be correct. However no warranty is made, either expressed or implied, regarding the accuracy of the results to be obtained from the use of such information. Test results are strictly according to IEC conditions. Capacities of batteries depend on drain, temperature and cut-off voltage. Data are subject to change.